



BITS HROCK LINHA DOWN-THE-HOLE

Punho		Diâmetros		Peso	Faces	Faces e Botões
		mm	pol	kg		
	MISSION	114	4 1/2"	8,0	Plana e Côncava	 FACE PLANA Para rocha semi dura, dura e fraturada.
		120	4 3/4"	8,5		
		140	5 1/2"	14,0		
		152	6"	21,0		
		156	6 1/8"	22,0		
		165	6 1/2"	24,0		
		203	8"	28,0		
		216	8 1/2"	29,0		
		254	10"	59,0		
	SD	165	6 1/2"	26,0	Plana, Côncava e Drop Center	 FACE CONVEXA Para rocha muito dura
		203	8"	43,0		
		216	8 1/2"	45,0		
		254	10"	53,0		
		305	12"	87,0		
		320	12 1/2"	90,0		
		355	14"	165,0		
		370	14 1/2"	178,0		
		381	15"	180,0		
	QL	114	4 1/2"	9,3	Plana e Côncava	 FACE CÔNCAVA Para todos os tipos de rocha
		120	4 3/4"	10,0		
		140	5 1/2"	12,5		
		152	6"	24,0		
		156	6 1/8"	24,3		
		165	6 1/8"	26,0		
		203	8"	35,0		
		216	8 1/2"	37,0		
		241	9 1/2"	52,0		
	DHD	254	10"	53,0	Plana e Côncava	 BOTÃO ESFÉRICO Para solos duros, abrasivos e grandes profundidades
		305	12"	87,0		
		89	3 1/2"	6,2		
		114	4 1/2"	9,3		
		120	4 3/4"	10,0		
		140	5 1/2"	12,5		
		152	6"	24,0		
		156	6 1/8"	24,3		
		165	6 1/2"	26,0		
		203	8"	35,0		
		216	8 1/2"	37,0		
		254	10"	53,0		
		305	12"	87,0		
		311	12 1/4'	90,0		
						 BOTÃO BALÍSTICO Para solos macios e homogêneos